

DuPont™ StoneTech® Professional Impregnator Pro® Sealer

TECHNICAL DATA SHEET



PRODUCT BENEFITS

- Heavy duty protection against most stains
- Preserves natural look
- Solvent-based formula
- Interior and exterior use

RECOMMENDED SURFACES

Natural stone such as granite, limestone, slate, travertine, bluestone and sandstone.

AVAILABLE SIZES

493ml, 946ml, 3.785L, 18.92L, 200L

COVERAGE

3sqm-30sqm per litre, depending on porosity of stone.

EXPECTED WEAR

3–5 years on interior surfaces and 1–3 years on exterior surfaces.

TECHNICAL INFORMATION

Form:	Liquid
Specific Gravity:	0.746
HMIS Rating:	2,2,0
Flash Point:	40°C

VOC CONTENT

734 g/L

The DuPont™ StoneTech® Professional product line complies with all federal, state and local VOC regulatory requirements and is packaged in containers with at least 25% post-consumer recycled material.

DISTRIBUTED BY:

Sareen Stone
86 Nirranda Street
Concord West, NSW Australia 2138
Ph: (02) 9736 1833 Fax: (02) 9736 2260
www.sareenstone.com.au

DuPont StoneTech® Professional
7 Eden Park Drive
Macquarie Park, NSW Australia 2113
(02) 9923 7307
www.chemicalsolutions.dupont.com.au

DIRECTIONS

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to applying sealer. Make sure surface is clean, dry and free of waxes and coatings. Surface temperature should be between 10°C and 27°C. Keep children and pets out of the area until foot traffic resumes.

1. Ensure area is well-ventilated during application and until the surface is dry. Use a respirator if unsure that area is well-ventilated. A NIOSH-approved respirator with a combination HEPA/organic vapor cartridge is recommended. Follow respirator manufacturer's instructions for use.
2. Mask any surfaces not intended to be treated.
3. Liberally apply an even coat using a paint pad, roller, brush or pump-up garden sprayer. **DO NOT USE A POWER SPRAYER.** See method of application for more information. Do not thin before using.
4. Allow sealer to penetrate surface for 15–30 minutes; denser stone may require more time for sealer to penetrate. During this time, distribute excess sealer over entire area to ensure even penetration. **DO NOT ALLOW EXCESS IMPREGNATOR PRO® TO DRY ON SURFACE.**
5. Thoroughly wipe entire surface with dry cloth to remove excess DuPont™ StoneTech® Professional Impregnator Pro® from surface.
6. A second coat may be needed for more porous surfaces and should be applied one hour after initial application, as directed in steps 3–5.
7. If excess sealer was not completely wiped off and a residue appears, wipe entire surface with a towel dampened with sealer. Use a white nylon scrubbing pad to loosen residue and follow with white absorbent towel to remove.
8. Full cure is achieved after 24–72 hours; foot traffic may begin in 6–8 hours. Cover with red rosin paper if foot traffic must resume before the recommended time periods have passed.
9. Rags and equipment that are wet with product may be combustible. Clean up promptly after job is complete. Clean equipment with mineral spirits and allow to dry in a well-ventilated area. Allow rags to dry in a well-ventilated area out of the reach of children and pets. When dry, dispose of in accordance with local waste disposal regulations.

METHOD OF APPLICATION:

DO NOT USE A POWER SPRAYER. Power sprayers increase exposure hazard. Power sprayers also create a significant amount of overspray resulting in wasted product and the need for additional clean-up. A pump-up garden sprayer will reduce the potential for over-exposure to vapors and produce better results.

For small jobs, use a paint pad, roller or brush. Trigger spray bottles are not recommended. Trigger sprayers create overspray and may not give a uniform application. Better results will be obtained using a pad, roller or brush.

For larger jobs, use a pump-up garden sprayer available at your local garden center, hardware store, or home improvement center.

STORAGE AND HANDLING INSTRUCTIONS

WARNING: COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED. Do not ingest. **HARMFUL VAPORS.** Avoid prolonged exposure to vapors. Use only in a well-ventilated area. For spray application, use a pump-up garden sprayer. **DO NOT USE A POWER SPRAYER.** Use a respirator if unsure that work area is well-ventilated. A NIOSH-approved respirator with a combination HEPA/organic vapor cartridge is recommended. Follow respirator manufacturer's instructions for use. **MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION.** Avoid contact with eyes and skin. Wear solvent-resistant gloves such as nitrile gloves. **KEEP OUT OF THE REACH OF CHILDREN.** Do not store above 100°F/38°C. Do not mix with other chemicals.

EMERGENCY/FIRST AID PROCEDURES

Ingestion: Do not induce vomiting. Call poison control center. Call a physician.

Eye Contact: Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if applicable, and continue flushing. Call a physician if eye irritation persists.

Skin Contact: Wash skin with mild soap and water. Call a physician if skin irritation persists. Launder affected clothing before re-wearing.

Inhalation: Remove to fresh air. Call a physician if irritation, nausea, dizziness or respiratory problems persist.

The information is furnished free of charge and based on information that DuPont believes to be generally reliable and accurate. Individual facts and circumstances may differ. It is intended for your use at your own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Copyright © 2008 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™, StoneTech®, and Impregnator Pro® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.

K-20508 (08/08)



The miracles of science™

PROTECT

CLEAN

TRANSFORM